



WHITE



61001
63002 61041
63012 61011 61021 61031

BEIGE



61581
63042 61591 61601 61611 61621 61631 61661

BLACK



61121
63092

METALLIC



62611



62621

YELLOW



61981

TRANSLUCENT



61111

GREEN



61781
63102



61791



61801



61811



61821



61831



61841



61881

BROWN



61141



61151



61181



61191



61201

BLUE



62201



62211



62221



62231



62241

BRONZE



61331
63082



61341
63072



61351



61361

GRAY



62401
63022



62411
63052



62421



62431



62441



62451



62461



62481



62491

CLAY



62051
63032



62061



62071



62081

RED



61501
63062



61431



61441



61451



61461



61471



61481



61491



61511

The sealant colors contained in this reference guide are produced by a printing process that may result in slight color variations. For critical color matching, apply sealant to a sample of the substrate, prior to use. It is the responsibility of the user to determine suitability of the product for the particular substrate. Colors are best viewed in natural daylight.

Colors in **Bold Red** are available in 20 oz. Sausage Packs.



WEATHERMASTER™
METAL ROOF SEALANT

Comparison Guide					
	METAL ROOF SEALANT	VOC Solvent	Silicone	Urethane	Tripolymer
Paintable	1-2 hour*	2-4 hours	No	2-7 days	24 hours
Shrinkage	1%	35%	5%	5%	50%
Flexibility	50%**	25%	25%	25%	25%
Cold Weather Extrusion	0°	20°	-35°	32°	40°
VOC-compliant	Yes	Yes	Yes	Yes	Yes
Solvent-Free	YES	No	Yes	No	No
Isocyanate-Free	YES	No	Yes	No	Yes
Earth Friendly	YES	No	Yes	No	No
Gap Filling	1"	1/2"	1/2"	1/2"	1/2"
Odor	Slight	Heavy	Mild	Mild	Heavy
Service Temperature (*F)	-75° to 300°	-20° to 200°	-45° to 350°	-40° to 180°	-40° to 180°

*Translucent is not paintable.
**Translucent is 25% flexible.

WEATHERMASTER™ METAL ROOF SEALANT

- 50+ available colors
- Bonds to wet surfaces
- Waterproof, UV-resistant
- Green build approved

Color availability is subject to change without notice. The sealant colors contained in this reference guide are produced by a printing process that may result in slight color variations. For critical color matching, apply sealant to a sample of the substrate, prior to use. It is the responsibility of the user to determine suitability of the product for the particular substrate. Colors are best viewed in natural daylight.

Refer to www.titebond.com for the WeatherMaster™ Metal Roof Color Match Cross-Reference Guide.
Refer to the Titebond Professional Caulks & Sealants Catalog for other products.

Franklin International

2020 Bruck Street Columbus, Ohio 43207

800.669.4583 Customer Service 800.347.4583 Technical Service
www.titebond.com 800.879.4553 FAX



WEATHERMASTER™
METAL ROOF SEALANT

Titebond
THE PRO'S ADVANTAGE

WEATHERMASTER™
METAL ROOF SEALANT

Extruded down to 0°F
Permanently flexible - Won't crack
Adheres to most construction materials
Cures in 15 min.

GREEN SEALANTS
SPRINK POLYMER TECHNOLOGY

CAUTION:
IRITANT. SKIN IRRITANT.
See MSDS on rear panel.
10.1 fl. oz. (300 mL)

Color Reference Guide