

SIDING, WINDOW & DOOR

WEATHERMASTER™

SEALANT

Comparison Guide

	WEATHERMASTER™	VOC Solvent	Silicone	Urethane	Tripolymer
Paintable	1 hour*	2 hours	No	2-7 days	24 hours
Shrinkage	1%	35%	5%	5%	50%
Flexibility	25%	25%	25%	25%	25%
Cold Weather Extrusion	0°	20°	-35°	32°	40°
VOC-compliant	Yes	Yes	Yes	Yes	Yes
Solvent-Free	YES	No	Yes	No	No
Isocyanate-Free	YES	No	Yes	No	Yes
Earth Friendly	YES	No	Yes	No	No
Gap Filling	1"	1/2"	1/2"	1/2"	1/2"
Odor	Slight	Heavy	Mild	Mild	Heavy
Service Temperature (*F)	-75° to 300°	-20° to 200°	-45° to 350°	-40° to 180°	-40° to 180°

*Translucent is not paintable.

WEATHERMASTER™

SEALANT

- 175+ available colors
 - Bonds to wet surfaces
 - Waterproof, UV-resistant
 - Green build approved

Color availability is subject to change without notice. The sealant colors contained in this reference guide are produced by a printing process that may result in slight color variations. For critical color matching, apply sealant to a sample of the substrate, prior to use. It is the responsibility of the user to determine suitability of the product for the particular substrate. Colors are best viewed in natural daylight.

Refer to www.titebond.com for the WeatherMaster™ Color Match Cross-Reference Guide.
Refer to the Titebond Professional Caulks & Sealants Catalog for other products.

Franklin International

2020 Bruck Street Columbus, Ohio 43207

800.669.4583 Customer Service

800.347.4583 Technical Service

www.titebond.com

800.879.4553 FAX

SIDING, WINDOW & DOOR

WEATHERMASTER™

SEALANT







Color Reference Guide



BROWN

44001 White	44021 Blue White	44041 Gray White	45501 Off White	45511 Antique White
44011 Translucent	43991 Clear	44031 Black		
44211	44221	44231	44251	44261
44271	44281	44291	44311	44321
44341	44371	44391	44441	44501
44051	44061	44071	45661	
45521	45561	45571	45581	45621
45631	45641	45671	45861	45871
49701	49751	49771	49791	49811
49841	49881	49851	49861	

RED BRONZE

BEIGE

45551	45751	46001	46011	46021
46031	46041	46051	46061	46071
46081	46091	46111	46121	46141
46151	46161	46171	46181	46191
46201	46211	46231	46241	46251
46261	46271	46281	46301	46311
46321	46341	46351	46361	46371
46381	46391	46421	46431	46451
46461	46471	46501	46571	

CLAY

44601	44611	44631	44641	44651
44661	44671	44681	44691	44701
44711	44721	44731	44741	44751
44761	44771	45781	45821	
45601	45651	45711	45731	45761
45771	45851	49201	49211	49221
49231	49241	49261	49271	49291
49301	49311	49321	49331	49341
49351	49371	49391		

GREEN

GRAY

45591	45691	45811	45841	46601
46631	46651	46661	46671	46681
46691	46711	46721	46751	46761
46771	46781	46791	46811	46841
46861	46881			
45531	45611	45681	45801	49401
49421	49441	49451	49491	49511
49521	49531	49541	49551	49561
45701	45831	49041	49051	49071
49091				

BLUE

YELLOW

The sealant colors contained in this reference guide are produced by a printing process that may result in slight color variations. For critical color matching, apply sealant to a sample of the substrate, prior to use. It is the responsibility of the user to determine suitability of the product for the particular substrate. Colors are best viewed in natural daylight.