

Vulkocell-Polcell

**Vulkollan® e
poliuretano aspanso**

Sponge Polyurethane & Vulkollan®

**SICUREZZA E RESISTENZA
ALLA COMPRESSIONE
SAFETY AND HIGH COMPRESSION
STRENGTH**



EUROFOAM

www.eurofoam.com



Vulkocell-Polcell

Struttura del materiale

- Lastre in Vulkollan® e in Poliuretano espanso a cellule chiuse

Caratteristiche tecniche

- Densità: da 300 Kg/m³ a 650 Kg/m³
- Deformabilità e resistenza alla compressione
- Resistenza ad olio e grasso
- Comportamento uniforme alla compressione in un campo di temperatura da -20 °C a +80 °C

Dimensioni standard

- Lastre: mm 250x500
- Spessore: da 2 a 65mm

Applicazioni

- Impiegati nella realizzazione di componenti ammortizzanti per l'industria automobilistica, ascensori, molle per stampi, barre di pressione

Structure of material

- Vulkollan® and Polyurethane closed cell foam sheets

Technical characteristics

- Density: from 300 Kg/m³ to 650 Kg/m³
- Deformability and compression strength
- Resistance to oils and fats
- Uniform behaviour with compression in a temperature field from -20°C to +80°C

Standard sizes

- Sheets: mm 250x500
- Thickness: from 2mm to 65mm

Application

- Used for the production of springs and shock-absorbing details in the automobile industry, seals for trunks and joints for ball bearings, pressure bars



EUROFOAM

via C. Colombo, 12 - 20020 Lainate (MI) Italy

Tel. ++39+2 93796660

Fax ++39+2 93796700

<http://www.eurofoam.com>

E-mail: info@eurofoam.com



EUROFOAM

è una Azienda certificata

UNI EN ISO 9001